Date Prepared: 12/18/02

MATERIAL SAFETY DATA SHEET/COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

SECTION I – PRODUCT IDENTIFICATION

GOO GONE CANDLE WAX LIFTER

CONTAINER SIZE: 2 fl oz

STOCK NO.: WL02

SUPPLIER'S NAME: MAGIC AMERICAN PRODUCTS, INC. ADDRESS: 23700 MERCANTILE ROAD; CLEVELAND, OH 44122 24 Hour Emergency Phone: CHEMTEL 1-800-255-3924 Information Phone: MAGIC AMERICAN PRODUCTS, INC.

M-F, 9-5 EST 1-800-321-6330

DOT SHIPPING INFORMATION	HAZARDS RATING INFORMATION			
DOT SHIPPING NAME: Not regulated		NFPA	NPCA(HMIS)	0-Minimal
DOT HAZARD CLASS: None DOT LABEL: None DOT PACKING GROUP: None	Health	0	1	1-Slight
	Flammability	1	2	2-Moderate
	Reactivity	0	0	3-Serious
	Personal Protection	N/A	C	4-Extreme
				C-Glasses, gloves, apron

SECTION II - INGREDIENTS

CAS NO. %WT 313/CHEMICAL PEL SKIN TWA/TLV CHEMICAL NAME CARCINOGEN Proprietary Mixture 100% N/A None No ingredients are N/A N/A (Detergent and Paraffin-based Stain Remover) regulated

All ingredients used in this proprietary mixture are listed on the TSCA Inventory List and none is listed as carcinogenic by OSHA, IARC or NTP.

SECTION III - PHYSICAL DATA

Boiling Point: 370°F Vapor Pressure: 43.7 mm Hg Solubility in Water: Partially Soluble

pH: None

Specific Gravity: 0.764 g/ml

Evaporation Rate: Negligible (ASTM D1901-85) Appearance/Odor: Colorless Liquid with Spicy Fragrance

VOC Content: 98.3% VOC by CARB

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: 156°F (69°C) (Pensky-Marten Closed Cup)

Explosive Hazard: N/D

Extinguishing Media: Foam, dry chemical, carbon dioxide, and water spray or fog.

Special Fire Fighting Procedures: Use self-contained breathing apparatus for respiratory protection in enclosed areas when fighting a fire or when

heated material becomes highly flammable.

Unusual Fire and Explosion Hazards: Not an oxidizer.

SECTION V – REACTIVITY DATA

Stability: Stable

Incompatibility: Keep away from oxidizing materials (i.e., chlorine, strong

acids).

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed during combustion.

Hazardous Polymerization: Will not occur.

SECTION VI – STORAGE AND HANDLING

KEEP OUT OF THE REACH OF CHILDREN

Store in a cool, well ventilated dry area away from heat or open flame and from devices capable of generating an electric spark.

Do not store at temperatures above 120°F.

SECTION VII - HEALTH EFFECTS AND FIRST AID

PRIMARY ROUTES OF ENTRY AND EFFECTS OF OVEREXPOSURE

EYES: According to the Federal Hazardous Substance Act testing protocol 16CFR 1500.42, and based upon laboratory tests on an analogous material, this product was shown not to be an eye irritant.

SKIN: According to the Federal Hazardous Substance Act testing protocol 16CFR 1500.41, and based upon laboratory tests on an analogous material, this product was shown not to be a primary skin irritant.

INHALATION: Not expected to be an inhalation hazard.

INGESTION: According to the Federal Hazardous Substance Act testing protocol 16CFR 1500.3(c)(2)(i), and based upon laboratory tests on an analogous material, this product was shown to be non-toxic by the oral route of exposure and is not considered an ingestion hazard. However, this product does contain petroleum distillates and is an aspiration hazard.

LONG TERM EFFECTS: No long term effects expected.

FIRST AID PROCEDURES

EYES: Remove any contact lenses and flush both eyes with cool running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN: Avoid repeated, excessive and prolonged daily skin contact. Wash with soap and water and apply skin cream or emollient.

INHALATION: Remove person to fresh air.

INGESTION: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and damage. Therefore, do not induce vomiting if ingestion occurs. Seek medical attention immediately.

SECTION VIII – SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: This product is not expected to be an inhalation hazard. In areas of inadequate ventilation, organic vapor cartridges are appropriate if respiratory protection is preferred by the handler.

VENTILATION: Mechanical (general) ventilation is usually adequate.

PROTECTIVE GLOVES: Chemically resistant gloves (neoprene) recommended for prolonged use.

EYE PROTECTION: Splash goggles are recommended where usage creates significant splashing.

SECTION IX – SPILL OR LEAK PRECAUTIONS

STEPS TO BE TAKEN IN CASE OF SPILLAGE OR LEAKAGE: Ventilate area. Spilled material can be picked up with sorbant material. Use caution where surfaces may become slippery from spilled material.

WASTE DISPOSAL METHOD: Follow proper methods for the disposal of large quantities of flammable materials.

WASTE DISPOSAL CAUTION: Hazardous substances cleaned with this product may create hazardous waste that must be properly characterized and disposed of in accordance with RCRA, state and local regulations.

N/A = NOT APPLICABLE N/E = NOT ESTABLISHED N/D = NOT DETERMINED<= LESS THAN > = MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is for Industrial and Institutional use only and considered accurate as of the date of publication. It is not necessarily all inclusive or fully adequate in every circumstance. The suggestions should not be confused with or followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product. Magic American assumes no responsibility for any product information placed on the Internet by individuals who are not affiliated with Magic American.